

ALPACA with PRODURATECT™ is manufactured to meet the following typical properties:

#### Specifications:

Width ..... 54"  
Roll Size ..... 30 yds  
Thickness ..... 1.0 mm  
Nominal Weight ..... 28 oz. per linear yd  
Contents ..... PVC  
Backing ..... Q1 Polyester  
Cold Crack ..... -10°F  
UV Stabilized Pigments ..... 500 hours minimum  
Abrasion Resistance<sup>†</sup>... Wyzenbeek (100K cycles #10 cotton duck)

#### Suggested Applications:

Contract, Hospitality, Office, Residential, Restaurant



This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

<sup>†</sup> Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

#### Meets Flammability Requirements\*:

California Technical Bulletin 117-2013, Section 1\*\*  
BIFMA, Class A  
UFAC, Class 1  
NFPA 260, Class 1

\*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

\*\* This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

#### Other Attributes:

Phthalate Free  
Flame Retardant Additive Free  
Anti-Microbial Additive Free

#### Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEXTM and Produratect™ are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.



**ENDURATEX™**  
We cover the world.

1181 California Ave, Suite 235, Corona, CA 92881 | 800.243.2472 | 951.332.4100  
f: 951.332.4076 | w: [enduratex.com](http://enduratex.com) | e: [cs@enduratex.com](mailto:cs@enduratex.com)  
Warehouse Locations: California, Tennessee

