

ANDANTE with  FORBID is manufactured to meet the following typical properties:

Specifications:

Width 54"
 Roll Size 30 yds
 Thickness 1.0 mm
 Nominal Weight 30 oz. per linear yd
 Contents 100% PVC
 Backing Q1 Polyester
 Cold Crack -10°F
 UV Stabilized Pigments 300 hours minimum
 Abrasion Resistance†...Wyzenbeek (100K cycles #10 cotton duck)

Meets Flammability Requirements*:

California Technical Bulletin 117-2013, Section 1**
 BIFMA, Class A
 UFAC, Class 1
 NFPA 260

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

Suggested Applications:

Corporate, Healthcare, Hospitality, Residential, Restaurant

Other Attributes:

Flame Retardant Additive Free
 Anti-Microbial Additive Free
 Phthalate Free
 CFFA-Healthcare-201 Certified



This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

† Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

FORBID™ Clean and Care Guide

 FORBID dramatically increases stain resistance while preserving the integrity of the fabric luster and softness.

Method One:

For mosts common stains, use mild soap and water.

Method Two:


If Method One doesn't work, use the following household items; FANTASTIK, 409 or MR.CLEAN.

Method Three:

For tougher stains such as permanent marker, paint and lipstick, use 70% isopropyl alcohol.

	STAINING AGENT							
	DIRT	PEN MARKS	SHARPIE	PAINT	KETCHUP & MUSTARD	LIPSTICK	NAIL POLISH	BLUE JEAN
METHOD 1	X	X						X
METHOD 2	X	X			X	X		X
METHOD 3		X	X	X	X	X	X	X

The Enduratex™ care guide addresses the performance of FORBID™ products as indicated in product testing, conducted under laboratory conditions. Results may vary. The information contained is not a guarantee and does not relieve the user of the responsibility of proper and safe use of recommended cleaning agents. The use of certain agents has been found to be harmful to the surface appearance and lifespan of vinyl. Please familiarize yourself with those products for best results. Enduratex™ topcoat, FORBID™, is resistant to most common stains, however existing dyes and pigments in some agents have been seen to create a permanent stain if not properly treated in a timely manner. Enduratex™ maintains the highest vinyl production standards. Anomalies may occur during finishing if the vinyl comes into contact with incompatible forms.

ENDURATEX™ and  FORBID are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.



1181 California Ave, Suite 235, Corona, CA 92881 | 800.243.2472 | 951.332.4100
 f: 951.332.4076 | w: enduratex.com | e: cs@enduratex.com
 Warehouse Locations: California, Tennessee