

ASPIRATIONS with PRODURATECT™ is manufactured to meet the following typical properties:

**Specifications:**

Width ..... 54"  
Roll Size ..... 30 yds.  
Thickness ..... 1.02 mm  
Nominal Weight ..... 27 oz. per linear yard  
Contents ..... PVC  
Backing ..... Polyester  
Cold Crack ..... -10°F  
UV Stabilized Pigments ..... 300 hours minimum  
Abrasion Resistance† ..... Wyzenbeek:  
(100K cycles #10 cotton duck)

**Meets Flammability Requirements\*:**

California Technical Bulletin 117-2013, Section 1\*\*  
NFPA 260, Class 1  
BIFMA, Class A  
UFAC, Class 1

\*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

\*\* This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1

**Suggested Applications:**

Healthcare, Hospitality, Marine Interior, Office,  
Residential, Restaurant, RV



This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

† Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

**Other Attributes:**

Flame Retardant Additive Free  
Phthalate Free  
Anti-Mildew Additive Free  
Anti-Microbial/Anti-Bacterial Additive Free

**Cleaning Instructions:**

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp.  
and may not be used without written permission of CGPC America Corp.



**ENDURATEX™**  
We cover the world.

4 Latitude Way, Suite 108, Corona, CA 92881 | 800.243.2472 | 951.332.4100  
fax: 951.332.4076 | [enduratex.com](http://enduratex.com) | [cs@enduratex.com](mailto:cs@enduratex.com)  
Warehouse Locations: California, Tennessee

