

BERWICK TWEED with PRODURATECT™ is manufactured to meet the following typical properties:

Specifications:

Width	54"
Roll Size	30 yds
Thickness	1.2 mm
Nominal Weight	25 oz. per linear yd
Contents	100% PVC
Backing	Polyester
Cold Crack	-10°F
UV Stabilized Pigments	500 hours minimum
Abrasion Resistance [†]	Wyzenbeek: (100K cycles #10 cotton duck)

Suggested Applications:

Gaming, Hospitality, Office, Residential, Restaurant



This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

[†] Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Meets Flammability Requirements*:

California Technical Bulletin 117-2013 Section 1**

BIFMA, Class A

UFAC, Class 1

NFPA 260, Class 1

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

Other Attributes:

Phthalate Free

Flame Retardant Additive Free

Anti-Mildew Additive Free

Anti-Microbial/Anti-Bacterial Additive Free

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp.
and may not be used without written permission of CGPC America Corp.

CFFA
CHEMICAL FABRICS & FILM
ASSOCIATION INC.



NEWH

AMERICAN
SOCIETY OF
INTERIOR
DESIGNERS
AS
INDUSTRY
PARTNER



ENDURATEX™
We cover the world.

enduratex.com | cs@enduratex.com
800.243.2472 | 951.332.4100 | fax: 951.332.4076
Warehouse Locations: California, Tennessee