

CAMO

CAMO with PRODURATECT™ is manufactured to meet the following typical properties:

Specifications:

Width 54"
Roll Size 30 yds
Thickness 1.10 mm
Nominal Weight 33 oz. per linear yd
Contents 100% PVC
Backing Brushed Polyester
Cold Crack -10°F
UV Stabilized Pigments 650 hours minimum
Abrasion Resistance[†] Wyzenbeek:
(100K cycles #10 cotton duck)

Meets Flammability Requirements*:

Motor Vehicle Safety Standard 302
California Technical Bulletin 117-2013 Section 1**
BIFMA, Class A
UFAC, Class 1
NFPA 260, Class

* This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

Suggested Applications:

Automotive, RV, Recreational, Residential, Office,
General Seating



This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

† Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp.
and may not be used without written permission of CGPC America Corp.



ENDURATEX™
We cover the world.

enduratex.com | cs@enduratex.com
800.243.2472 | 951.332.4100 | fax: 951.332.4076
Warehouse Locations: California, Tennessee