

ENDURATEX™ WITH *Produratect™ A*

DOESKIN with *Produratect™ A* is manufactured to meet the following typical properties*:

Width	54"
Roll Size	40 yards
Nominal Weight	32 oz. per lin. yard
Contents	100% Virgin Vinyl
Cold Crack	-10°F
UV Stabilized Pigments	300 hour minimum
Abrasion	Heavy Duty-Wyzenbeek
Class Ratings	ASTM D-3690 Class A
Thickness	Approximately 1.02 mm
Heat Sealable	Yes

Compatible with commercially available adhesives.

Meets flammability requirements*:

- Motor Vehicle Safety Standard 302
- California Technical Bulletin 117 Section E

*This term and any corresponding data refer to typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual conditions.

Suitable Applications:

- RV/Automotive
- Office/General Seating
- Residential Seating
- General Sewn Products

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and ***Produratect™ A*** are trademarks of CGPC America, Corp. and may not be used without written permission of CGPC America, Corp.



CGPC is a certified
QS-9000/ISO 9002
Manufacturer



CGPC AMERICA CORPORATION

19445 E. Walnut Drive East, Industry, CA 91789 • 800/243-2472 • 909/594-0080

Order Desk Fax 909/594-0172 • Visit Our Web Site: www.cgpcamerica.com • E-Mail: cs@cgpcamerica.com

Warehouse Locations: Industry • Atlanta • Dallas • Cincinnati