

DUET with PRODURATECT™ is manufactured to meet the following typical properties:

Specifications:

Width 54"
 Roll Size 30 yds
 Thickness 1.10 mm
 Nominal Weight 27 oz. per linear yd
 Contents 100% PVC
 Backing Brushed Polyester
 Cold Crack -10°F
 UV Stabilized Pigments 300 hours minimum
 Abrasion Resistance† Wyzenbeek:
 (100K cycles #10 cotton duck)

Suggested Applications:

Corporate, Healthcare, Hospitality, Office,
 Residential, Restaurant



This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

† Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Meets Flammability Requirements*:

California Technical Bulletin 117-2013 Section 1**
 BIFMA, Class A
 UFAC, Class 1
 NFPA 260, Class 1

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

Other Attributes:

Phthalate Free
 Flame Retardant Additive Free
 Anti-Mildew Additive Free
 Anti-Microbial/Anti-Bacterial Additive Free

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp.
 and may not be used without written permission of CGPC America Corp.



ENDURATEX™
 We cover the world.

enduratex.com | cs@enduratex.com
 800.243.2472 | 951.332.4100 | fax: 951.332.4076
 Warehouse Locations: California, Tennessee