

LIGHTHOUSE

LIGHTHOUSE with PRODURATECT™ M is manufactured to meet the following typical properties:

Specifications:

Width	54"
Roll Size	40 yds
Thickness	0.97 mm
Nominal Weight	28 oz. per Lin. yard
Contents	100% PVC
Backing	100% Polyester
Cold Crack	-10°F
UV Stabilized Pigments	500 hours minimum
Pink Stain Resistant (ASTM E1428)	Pass
Abrasion Resistance	Wyzenbeek (50K cycles #10 cotton duck)
Heat Sealable	Yes
Mildew Resistance (ASTM G-21)	Pass
Anti-Bacterial/Anti-Microbial (AATCC 147)	Pass

This product has been treated with anti-bacterial and anti-microbial agents that will provide resistance to the following:

(AATCC Test Method 147)

Bacillus Mycoides, Klebsiella Pneumoniae, Proteus Vulgaris, Staphylococcus Aureus, Salmonella Choleraesuis, Bacillus Cerus, Enterococcus Faecalis, Escherichia Coli

Suggested Applications:

Marine



* This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.



ENDURATEX™
We cover the world.



1181 California Ave, Suite 235, Corona, CA 92881 | 800.243.2472 | 951.332.4100
f: 951.332.4076 | w: enduratex.com | e: cs@enduratex.com
Warehouse Locations: California, Tennessee