



LONGITUDE

ENDURASOFT™ PREMIUM COLLECTION

ENDURATEX™ and PRODURATECT™ A are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.

LONGITUDE with **PRODURATECT™ A** top finish and featuring **ENDURATEX™ Q1** backing is manufactured to meet the following typical properties:

Width	54"
Roll Size	30 yds.
Nominal Weight	30 oz. per lin. yard
Contents	100% virgin vinyl
Cold Crack	-10°F
UV Stabilized Pigments	300 hours minimum
Abrasion Resistance	Heavy Duty Wyzenbeek
Class Ratings	ASTM D-3690 Class A
Thickness	Approximately 1.02 mm
Heat Sealable	Yes

Compatible with commercially available adhesives.

Suggested Applications:
 RV/Automotive
 Office/General Seating
 Residential Seating

Meets flammability requirements*:
 Motor Vehicle Safety Standard 302
 California Technical Bulletin 117 Section E

Cleaning instructions:
 This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions



ENDURATEX™
"We Cover The World"

11310 Harrel Street, Mira Loma, CA 91752 • 800/243/2472 • 951/332/4100
 Order Desk Fax: 951/332/4076 • cs@enduratex.com
 Warehouse Locations: California • Alabama • Ohio
www.enduratex.com