

**HONDA / MERCEDES / NISSAN / TOYOTA**

**HONDA, MERCEDES, NISSAN and TOYOTA** with  **FORBID**  
are manufactured to meet the following typical properties:

Width .....	54"
Roll Size .....	30 yds.
Nominal Weight .....	30 oz. per lin. yd.
Contents .....	100% Virgin Vinyl
Cold Crack .....	-10°F
UV Stabilized Pigments .....	500 hours minimum
Abrasion Resistance .....	Heavy Duty Wyzenbeek
Class Rating .....	ASTM D-3690 Class A
Thickness .....	1.02 mm
Heat Sealable .....	Yes

*Compatible with commercially available adhesives.*

**Suggested Applications:** Automotive, Conference Room, Residential Seating, Home Office,  
Lounge Seating, Residential

Oil and Sulfide Resistant

**Meets flammability requirements\*:** Federal Specification CCC-A-680-A  
Motor Vehicle Safety Standard 302  
California Technical Bulletin 117-2013, Section 1

\*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

 **FORBID** dramatically increases the stain resistance, while preserving the integrity of the fabric luster and softness.

 **FORBID** Cleaning instructions:

**Method One:** For most common stains and spills, use mild soap and water.

**Method Two:** If Method One doesn't work, use the following household items - FANTASTIK • 409 • MR. CLEAN.

**Method Three:** For tougher stains such as sharpie, paint and lipstick, use a 70% isopropyl alcohol wipe.

For more information, please visit [www.forbidart.com](http://www.forbidart.com)

CLEANING METHOD	STAINING AGENT								
	GREASE	FOOD MARKS	LIQUIDS	MARKS	WAXES	WATER-BASED	LIQUOR	INK	SLURRY
METHOD 1	X	X							
METHOD 2	X	X	X	X	X	X	X	X	X
METHOD 3				X	X	X	X	X	X

The Enduratex™ care guide addresses the performance of FORBID products as indicated in product testing, conducted under laboratory conditions. Results may vary under actual conditions. The information contained in the care guide is not a guarantee and does not relieve the user of the responsibility of proper and safe use of the product and the use of recommended cleaning agents. The use of certain agents has been found to be harmful to the surface appearance and integrity of vinyl. Please familiarize yourself with these substrates for best results. Enduratex™ vinyl, FORBID, is resistant to most common stains; however, waxing dye and pigments in some staining agents have been seen to create a permanent stain if not properly treated in a timely manner. Enduratex™ maintains the highest vinyl production standards. Accidents may occur during finishing if the vinyl comes into contact with incompatible items.

**ENDURATEX™** and  **FORBID** are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.



11310 Harrel Street, Mira Loma, CA 91752 • 800/243-2472 • 951/332-4100  
Order Desk Fax: 951/332-4076 • Visit Our Website: [www.enduratex.com](http://www.enduratex.com) • Email: [cs@enduratex.com](mailto:cs@enduratex.com)  
Warehouse Locations: California • Alabama • Ohio

