

NATURAL MOVEMENTS with PRODURATECT™ PLUS
is manufactured to meet the following typical properties:

Width	54"
Roll Size	30 yds.
Nominal Weight	29 oz. per Lin. yard
Contents	100% PVC
Backing	Polyester/Rayon
Cold Crack	(-)10°F
Abrasion Resistance	Wyzenbeek (50,000 cycles #10 cotton duck) Taber (4.5 ASTM D 3884)
Thickness	1.02 mm
Mildew Resistant (Front and Back)	Pass
Anti-Bacterial/Anti-Microbial (AATCC 147 / ASTM G-21)	Pass

Compatible with commercially available adhesives.

Suggested Applications:

Office Interior, Hospitality, Restaurant, Healthcare, Gaming, Residential, RV, Marine Interior.

Meets flammability requirements*:

- Motor Vehicle Safety Standard 302
- California Technical Bulletin 117-2013, Section 1
- New York and New Jersey Port Authority
- Federal Aviation Specification 25.853
- Boston Fire Department Code
- NFPA 260 Class 1
- BIFMA Class A
- UFAC Class A

This product has been treated with anti-bacterial and anti-microbial agents that will provide resistance to the following:
(AATCC Test Method 147)

- | | |
|-----------------------|-------------------------|
| Bacillus Mycoides | Staphylococcus Aureus |
| Klebsiella Pneumoniae | Salmonella Choleraesuis |
| Proteus Vugaris | Bacillus Cerus |
| Enterococcus Faecalis | Escherichia Coli |

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Cleaning Instructions:

This product should be cleaned with mild soap and water.
Do not use alcohol based cleaners.

ENDURATEX™ and PRODURATECT™ PLUS are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.



ENDURATEX™
We cover the world.

1860 Compton Ave, Suite 101, Corona, CA 92880 | 800.243.2472 | 951.332.4100
Order Desk Fax: 951.332.4076 | Visit Our Website: www.enduratex.com | Email: cs@enduratex.com
Warehouse Locations: California | Alabama | Ohio

