

# PHANTOM

**PHANTOM** with **PRODURATECT™** top finish and featuring **ENDURATEX™ Q1** is manufactured to meet the following typical properties:

Width .....	54"
Roll Size .....	30 yds.
Nominal Weight .....	33 oz. per lin. yd.
Cold Crack .....	-10°F
UV Stabilized Pigments .....	300 hours minimum
Abrasion Resistance .....	Wyzenbeek (50,000 cycles #10 cotton duck)
Class Ratings .....	ASTM D 3690 - Class A
Thickness .....	1.3 mm
Mildew Resistant (Front and Back) .....	Pass

*Compatible with commercially available adhesives.*


**Suggested Applications:** Conference Room, Executive Seating, Hospitality, Lounge Seating, Restaurant Seating, RV/Automotive, Office / General Seating, Residential Seating

**Meets Flammability Requirements\*:** Motor Vehicle Safety Standard 302  
California Technical Bulletin 117-2013, Section 1  
BIFMA Class A  
UFAC Class 1  
NFPA 260

\*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

**Cleaning Instructions:** This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.\*

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.



11310 Harrel Street, Mira Loma, CA 91752 • 800/243-2472 • 951/332-4100  
Order Desk Fax: 951/332-4076 • Visit Our Website: [www.enduratedx.com](http://www.enduratedx.com) • Email: [cs@enduratedx.com](mailto:cs@enduratedx.com)  
Warehouse Locations: California • Alabama • Ohio

