

RENEW with PRODURATECT™ is manufactured to meet the following typical properties:

Specifications:

Width	54"
Roll Size	30 yds.
Thickness	0.88 mm
Nominal Weight	22 oz. per linear yard
Contents	TPO with PU Topskin
Backing	Tricot Knit Polyester
Cold Crack	-10°F
UV Stabilized Pigments	300 hours minimum
Abrasion Resistance†... Wyzenbeek (100K cycles #10 cotton duck)	
Mildew Resistance (ASTM G-21)	Pass
Anti-Bacterial/Anti-Microbial (AATCC 147)	Pass

Suggested Applications:

Corporate, Healthcare, Hospitality, Residential, Restaurant



This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

† Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Meets Flammability Requirements*:

No Fire Retardants were added to this product. Renew inherently meets the below requirements.

- Motor Vehicle Safety Standard 302
- California Technical Bulletin 117-2013, Section 1**
- NFPA 260 Class 1
- UFAC, Class 1
- BIFMA, Class A

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

This product has been treated with anti-bacterial and anti-microbial agents that will provide resistance to the following:

(AATCC Test Method 147)

- Bacillus Mycoides, Klebsiella Pneumoniae, Proteus Vulgaris, Staphylococcus Aureus, Salmonella Choleraesuis, Bacillus Cereus, Enterococcus Faecalis, Escherichia Coli

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.



ENDURATEX™
We cover the world.



1181 California Ave, Suite 235, Corona, CA 92881 | 800.243.2472 | 951.332.4100
f: 951.332.4076 | w: enduratex.com | e: cs@enduratex.com
Warehouse Locations: California, Tennessee