

SONOMA
is manufactured to meet the following typical properties:

Width	54"
Roll Size	25 yds
Thickness	1.6 mm
Nominal Weight	37 oz. per lin. yard
Contents	Upcycled Leather
Cold Crack	-10°F
Abrasion Resistance	Wyzenbeek (100,000 cycles #10 cotton duck)
UV Stabilized Pigments	300 hours minimum

Suggested Applications:
Automotive, Contract, Home Furnishings, Hospitality, RV

Meets flammability requirements*:
California Technical Bulletin 117-2013, Section 1**
NFPA 260, Class 1
Motor Vehicle Safety Standard 302
BIFMA, Class A
UFAC, Class 1

Cleaning Instructions:
This product should be cleaned with mild soap and water.
Do not use alcohol based cleaners.

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

**This product when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

ENDURATEX™ is a trademark of CGPC America Corp. and may not be used without written permission of CGPC America Corp.

IIDA International Interior Design Association
act
AMERICAN SOCIETY OF INTERIOR DESIGNERS
INDUSTRY PARTNER
CFFA CHEMICAL FABRICS & FILM ASSOCIATION INC.
WENBER National Association of Decorative Fabric Distributors
INTERNATIONAL CERT
CGPC is a certified ISO 9001:2009 Manufacturer
NEWH 2015 Corporate Partner
autocare ASSOCIATION Independence drives us.

ENDURATEX
We cover the world.

1181 California Ave., Suite 235, Corona, CA 92681 | 800.243.2472 | 951.332.4100
Order Desk Fax: 951.332.4076 | Visit Our Website: www.enduratex.com | Email: cs@enduratex.com
Warehouse Locations: California | Tennessee

