

VIRTUE with PRODURATECT™ is manufactured to meet the following typical properties:

Specifications:

Width 54"
 Roll Size 30 yds.
 Thickness 1.0 mm
 Nominal Weight 28 oz. per linear yard
 Contents 100% PVC
 Backing Q1 Polyester
 Cold Crack -10°F
 UV Stabilized Pigments 500 hours minimum
 Abrasion Resistance† Wyzenbeek:
 (100K cycles #10 cotton duck)

Suggested Applications:

Hospitality, Healthcare, Restaurant, Lounge, Office, Corporate, Residential, RV



This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

† Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Meets Flammability Requirements*:

California Technical Bulletin 117-2013, Section 1**
 BIFMA, Class A
 UFAC, Class 1
 NFPA 260, Class 1

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

Other Attributes:

Phthalate Free
 Flame Retardant Additive Free
 Anti-Mildew Additive Free
 Anti-Microbial/Anti-Bacterial Additive Free

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™, PRODURATECT™ and puretexas are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.



ENDURATEX™

We cover the world.



4 Latitude Way, Suite 108, Corona, CA 92881 | 800.243.2472 | 951.332.4100
 fax: 951.332.4076 | enduratex.com | cs@enduratex.com
 Warehouse Locations: California, Tennessee