

VISIONS

VISIONS with PRODURATECT™ is manufactured to meet the following typical properties:

Specifications:

| | |
|--|---|
| Width | 54" |
| Roll Size | 30 yds |
| Thickness | 1.12 mm |
| Nominal Weight | 26 oz. per linear yd |
| Contents | 100% PVC |
| Backing | Polyester |
| Cold Crack | -10°F |
| UV Stabilized Pigments | 500 hours minimum |
| Mildew Resistant (ASTM G-21) | Pass |
| Anti-Bacterial/Anti-Microbial (AATCC 147)..... | Pass |
| Abrasion Resistance† | Wyzenbeek: (100K cycles #10 cotton duck) |

Meets Flammability Requirements*:

California Technical Bulletin 117-2013 Section 1**
BIFMA, Class A
UFAC, Class 1
NFPA 260, Class 1
Boston Fire Code

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

Other Attributes:

Oil and Sulfide Resistant

Suggested Applications:

Corporate, Healthcare, Hospitality, Office,
Residential, Restaurant, Automotive/RV, Spa



This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

† Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp.
and may not be used without written permission of CGPC America Corp.



ENDURATEX™
We cover the world.

enduratex.com | cs@enduratex.com
800.243.2472 | 951.332.4100 | fax: 951.332.4076
Warehouse Locations: California, Tennessee